

Order No.: 56TP1M0C0ZV00190XX | **GTIN (EAN):** 4058352509852

Product description: Lic,multiadapter,alu,wh



Licross®, rail insert, adapter,with plug, 5-pole, with phase selection, mains connection: 230V, AC, 50/60Hz, terminal,5-pole, max. 2.5mm², multi adapter, of aluminium, coated, white, for IP64 protection rating, length: 500mm, width: 124mm, height: 68mm, multifunctional insert, protection rating (complete): IP64, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece

IP 64  

Wt. (kg): 0.8
GTIN (EAN): 4058352509852

Order No.: 56TP1M0C0ZV00190XX | GTIN (EAN): 4058352509852

Detailed technical description: Lic,multiadapter,alu,wh



Key data

- System family: Licross®
- Product type: rail insert
- Product name: Licross®
- Order No.: 56TP1M0C0ZV00190XX

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: internal wiring halogen-free, for trunking rail, 7..14-core, max. 0.5A

Certificates, Standards

- Protection rating: IP64
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- multi adapter: aluminium, coated, white, for IP64 protection rating
- Colour specification: white

Mounting

- Mounting height: object related (mounting location without light from other sources)
- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

- Length: 500mm
- Width: 124mm
- Height: 68mm
- Weight: 0.8kg