

Order No.: 5XA779120000BA | **GTIN (EAN):** 4058352556405

Product description: FL11mxpro,ECGunit,Lo,DA,IC1



Floodlight FL 11 maxi pro ECG unit; brightness control: DALI (with two DALI addresses); with terminal, 8-pole, max. 2.5mm², mains connection: 220..240V/380..400V AC, surge voltage resistance: line to ground: 10kV, dimming range 10..100%, LED unit replaceable on mast without ESD environment, LED unit replaceable, dustproof LED unit, LED unit replaceable without ESD environment, no afterglow with DALI off / DMX off command, ECG replaceable separately; ECG unit ECG unit of diecast aluminium, uncoated natural; length: 500mm / width: 152mm / height: 77mm; uncoated, natural, equipment: Longlife, insulation class (complete): insulation class I (protective earthing); certification: CE; permissible storage temperature: - 40..+85°C packaging unit: 1 piece



Wt. (kg): 5.6
GTIN (EAN): 4058352556405

Order No.: 5XA779120000BA | **GTIN (EAN):** 4058352556405

Detailed technical description: FL11mxpro,ECGunit,Lo,DA,IC1



Key data

- Product type: ECG unit
- Product name: Floodlight FL 11 maxi pro
- Order No.: 5XA779120000BA

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI (2 addresses)

Certificates, Standards

- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- ECG unit: diecast aluminium, uncoated, natural

Electrical connection

- Connection: terminal, 8-pole, max. 2.5mm²
- Nominal voltage: 220..240V/380..400V, AC
- Surge voltage resistance: line to ground: 10kV

Dimensions, Weight

- Length: 500mm
- Width: 152mm
- Height: 77mm
- Weight: 5.6kg

Service life

- Rated service life: 50000h (L95/B10) at AT = 25°C, 100000h (L96/B10) at AT = 10°C