

Order No.: 5XA779110000BA | **GTIN (EAN):** 4058352556375

Product description: FL11mx,ECGunit,Lo,DA,IC1



Floodlight FL 11 maxi ECG unit; colour temperature: 4000K, brightness control: DALI (with two DALI addresses); with terminal, 8-pole, max. 2.5mm², mains connection: 220..240V/380..400V AC, surge voltage resistance: line to ground: 10kV, dimming range 10..100%, LED unit replaceable on mast without ESD environment, LED unit replaceable, dustproof LED unit, LED unit replaceable without ESD environment, no afterglow with DALI off / DMX off command, ECG replaceable separately; ECG unit ECG unit of diecast aluminium, uncoated natural; length: 500mm / width: 152mm / height: 77mm; uncoated, natural, equipment: Longlife, protection rating (complete): IP66; insulation class (complete): insulation class I (protective earthing); certification: CE, ENEC, VDE; ball protection: ball impact resistant, only for outdoor installations, rated ambient temperature 10°C, permissible operating ambient temperature: -40..+30°C, permissible storage temperature: -40..+85°C packaging unit: 1 piece



Wt. (kg): 5.6
GTIN (EAN): 4058352556375

Order No.: 5XA779110000BA | **GTIN (EAN):** 4058352556375

Detailed technical description: FL11mx,ECGunit,Lo,DA,IC1



Key data

- Product type: ECG unit
- Product name: Floodlight FL 11 maxi
- Order No.: 5XA779110000BA

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Colour temperature: 4000K

Operating device:

- Control: DALI (2 addresses)

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): -40..+30°C
- Supplement: only for outdoor installations, rated ambient temperature 10°C
- Certification, designation: CE, ENEC, VDE

Material, Colour

- ECG unit: diecast aluminium, uncoated, natural

Electrical connection

- Connection: terminal, 8-pole, max. 2.5mm²
- Nominal voltage: 220..240V/380..400V, AC
- Surge voltage resistance: line to ground: 10kV

Dimensions, Weight

- Length: 500mm
- Width: 152mm
- Height: 77mm
- Weight: 5.6kg

Light emission

- Light emission: 0% at 0° inclination

Service life

- Rated service life: 50000h (L95/B10) at AT = 25°C, 100000h (L96/B10) at AT = 10°C

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 27.02.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -