


**Order No.:** 5XA769SCST | **GTIN (EAN):** 4058352556320


**Product description:** SConSp,psh.btn.interf,locCtrl,pushb.inp



SITECO Connect Sportpush button interface, local control - self-sufficient standalone sensors, configuration via Casambi app, installation type: lay-in mounting, recessed, installation location: in housing, of plastic, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, voltage: 230V, voltage type: AC, cable length: 0,1 m, 4 x push button input, Bluetooth®, packaging unit: 1 piece

IP 66  

Wt. (kg): 0.1  
GTIN (EAN): 4058352556320




It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 5XA769SCST | **GTIN (EAN):** 4058352556320

**Detailed technical description:** SConSp,psh.btn.interf,locCtrl,pushb.inp



## Key data

- Product type: lighting management components
- Product name: SITECO Connect Sport
- Order No.: 5XA769SCST

## Lighting technology | Lamps | Control gear

### Component 1

#### Lamps:

- Rated input power: 2W

#### Operating device:

- Control: Casambi, configuration via Casambi app

#### Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE

#### Material, Colour

- housing: plastic, black
- Colour specification: black

#### Mounting

- Mounting method, mounting location: recessed, lay-in mounting, in housing

#### Electrical connection

- Connection: cable, 2x 1.0mm<sup>2</sup>
- Nominal voltage: 230V, 50/60Hz, AC

#### Dimensions, Weight

- Weight: 0.1kg

#### Inputs

##### 4x push button input

- Range: max. 100m in open field
- Option: controllable via smartphone


#### Outputs

##### Bluetooth®

- Range: max. 100m in open field

**Order No.:** 5XA769SCST | **GTIN (EAN):** 4058352556320

**Dimensions:** SConSp,psh.bttm.interf,locCtrl,pushb.inp



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -