

Order No.: 56TL1MDSD1B | **GTIN (EAN):** 4058352542422

Product description: Licens,lightsens



Licross®light sensor D1, slave, central control - connection to lighting or building management, local control - self-sufficient standalone sensors, dimmable, installation location: to the Licross® trunking rail, of sheet steel, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, UKCA, voltage: 120..277V, voltage type: AC, 1 x light sensor, 1 x DALI-2, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.5
GTIN (EAN): 4058352542422

Order No.: 56TL1MDSD1B | **GTIN (EAN):** 4058352542422

Detailed technical description: Licensens,lightsens



Key data

- System family: Siteco Connect 11, SITECO Connect 22
- Product type: sensor
- Product name: Licross®
- Order No.: 56TL1MDSD1B

1x light sensor

- Connection: light sensor
- Illuminance: 20..800lx
- Option: usability at high altitudes

Lighting technology | Lamps | Control gear

Component 1

Lamps:

- Supplement: internal wiring halogen-free

Operating device:

- Control: DALI 2, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0..+50°C
- Certification, designation: CE, UKCA

Material, Colour

- sensor module: sheet steel, coil coated, white
- Colour specification: white

Mounting

- Mounting height: 4..12m
- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: plug, 5-pole, with phase selection
- Nominal voltage: 120..277V, 50/60Hz, AC

Dimensions, Weight

- Length: 500mm
- Width: 96mm
- Height: 97mm
- Weight: 0.5kg

Inputs

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 09.04.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -