

Order No.: 5XC3H41E08ME | GTIN (EAN): 4058352584217

Product description: SL11iQmd,ST0.5ST0.5,18720lm740,Comf



Streetlight SL 11 iQ midi, mast luminaire, primary light control with 3 zone faceted reflector, of plastic, silver coated, highly specular, primary optical cover: cover, of PMMA, transparent, light distribution: ST0.5ST0.5, light emission: direct distribution, primary light characteristic: asymmetric, installation type: post-top, side-entry, LED, High Power LED, rated luminous flux: 18.720lm, luminous efficacy: 150lm/W, light colour: 740, colour temperature: 4000K, control: optimised constant luminous flux control (CLO 2.0), Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), Light-Fading, Smart-Wire, Night-Set, Lumen-Switch, Temp-Guard, Auto-Match, with cable H07RN-F 5x 1.5mm², mains connection: 230..240V, AC, 50/60Hz, connection cable pre-assembled, cable length: 12,5m, start of lifetime: 125W, end of service life: 132W, reduction: 57W, luminaire housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), please order mast flange separately, inclination adjustable without tools: 0°, 5°, 10°, 15° (post-top) | 0°, -5°, -10°, -15° (side-entry), sealing non-destructively replaceable, multi-level sealing system, length: 780mm, width: 376mm, height: 118mm, mast flange for spigot size: 42mm (side-entry): 5XC10008XM4, 60/48mm (side-entry/post-top): 5XC10108XM2, 76/60mm (side-entry/post-top): 5XC10108XM1, equipment: Power, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, impact resistance: IK09, permissible operating ambient temperature for outdoor applications: -25..+50°C, standard-compliant lighting for roads and squares, Environmental Product Declaration (EPD) tested and certified by an independent institute, packaging unit: 1 piece



Lamps: LED
 Wt. (kg): 11.5
 GTIN (EAN): 4058352584217



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 22.03.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5XC3H41E08ME | GTIN (EAN): 4058352584217

Detailed technical description: SL11iQmd,ST0.5ST0.5,18720lm740,Comf



Key data

- Product type: mast luminaire
- Product name: Streetlight SL 11 iQ midi
- Order No.: 5XC3H41E08ME

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: 3 zone faceted reflector of plastic, silver coated, highly specular
- Cover: cover, transparent
- Light distribution: ST0.5ST0.5
- Beam angle: wide distribution with rear light component
- Symmetry: asymmetric distribution
- Light emission: direct distribution

Lamps:

- Lamps: with High Power LED, LED
- Rated luminous flux: 18720lm
- Luminous efficacy: 150lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 70
- Light colour: 740
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 5 SDCM (initial)
- Rated input power begin service life: 125
- Rated input power end service life: 132
- Rated input power at 50% lumin. flux: 57

Operating device:

- Control: iQ-Comfort
- Equipment: optimised constant luminous flux control (CLO 2.0), Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), Light-Fading, Smart-Wire, Night-Set, Lumen-Switch, Temp-Guard, Auto-Match

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK09
- Temperature range (operation): -25..+50°C
- Supplement: standard-compliant lighting for roads and squares
- Certification, designation: CE, ENEC, VDE
- EPD: Environmental Product Declaration (EPD) tested and certified by an independent institute

Material, Colour

- luminaire housing: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), please order mast flange separately, inclination adjustable without tools: 0°, 5°, 10°, 15° (post-top) | 0°, -5°, -10°, -15° (side-entry), sealing non-destructively replaceable, multi-level sealing system
- Colour specification: Siteco® metallic grey (DB 702S)
- Cover: cover of PMMA

Mounting

- Mounting method, mounting location: side-entry, post-top, on mast

Electrical connection

- Connection: cable H07RN-F 5x 1.5mm²
- Nominal voltage: 230..240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)
- Connection cable: pre-assembled, L= 12.5m

Dimensions, Weight

- Length: 780mm
- Width: 376mm
- Height: 118mm
- Weight: 11.5kg
- Mast spigot: mast flange for spigot size: 42mm (side-entry): 5XC10008XM4, 60/48mm (side-entry/post-top): 5XC10108XM2, 76/60mm (side-entry/post-top): 5XC10108XM1

Order No.: 5XC3H41E08ME | **GTIN (EAN):** 4058352584217

Detailed technical description: SL11iQmd,ST0.5ST0.5,18720lm740,Comf



Light emission

- Light emission: 0% at 0° inclination

Service life

- Rated service life: 100000h (L96/B10)
at AT = 25°C

Order No.: 5XC3H41E08ME | GTIN (EAN): 4058352584217

Dimensions: SL11iQmd,ST0.5ST0.5,18720lm740,Comf

