

Order No.: 51DR107DGBA | GTIN (EAN): 4058352509920 Product description: Lun41Flat,Ø150,1250Im830/840,0/1wh






Lunis 41 Flat, downlight, light emission: direct distribution, LED rated luminous flux: 1.250lm, light colour: 830/840, control gear: ECG, mains connection: 230V, AC, 50/60Hz, housing, round, of aluminium, coated, traffic white (RAL 9016), diameter: 170mm, protection rating (complete): IP20, protection rating (on room side): IP44, insulation class (complete): insulation class II (safety insulation), certification: CE, permissible ambient temperature for indoor applications: -20..+40°C, packaging unit: 1 piece

IP 20 □ (∈

Lamps: LED Wt. (kg): 0.3

GTIN (EAN): 4058352509920





Order No.: 51DR107DGBA | GTIN (EAN): 4058352509920

Detailed technical description: Lun41Flat,Ø150,1250lm830/840,0/1wh



Key data

- Product type: downlight - Product name: Lunis 41 Flat
- Order No.: 51DR107DGBA

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light emission: direct distribution

Lamps:

- Lamps: with LED
- Rated luminous flux: 1250lm
- Luminous efficacy: 83lm/W
- Colour temperature: 3000/4000K - Colour rendering index: CRI > 80
- Light colour: 830/840
- Rated input power: 15W

Operating device:

- Control gear: ECG
- Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Protection rating (on room side): IP44
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): -20..+40°C
- Certification, designation: CE

Material, Colour

- housing: aluminium, coated, traffic white (RAL 9016), round
- Colour specification: traffic white (RAL 9016)

Mounting

- Mounting method, mounting location: recessed, in the ceiling
- Ø of ceiling cut-out: 150mm
- Arrangement: single arrangement

Electrical connection

- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

- Diameter: 170mm - Height: 19mm - Weight: 0.3kg

- Rated service life: 30000h (L70/B50) at $AT = 25^{\circ}C$

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 10.10.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -



Order No.: 51DR107DGBA | GTIN (EAN): 4058352509920

Dimensions: Lun41Flat,Ø150,1250lm830/840,0/1wh

