


Order No.: 5TR10270Q | GTIN (EAN): 4039806496287 Product description: Mod,trunk.rail,2lg,L2990,7x2.5²,wh

Modario®, trunking rail, of sheet steel, coated, pure white, 2-length, length: 2.990 mm, width: 58 mm, height: 43mm, through-wiring: 7x 2.5mm², with terminal, 7-pole, max. 2.5mm², protection rating (complete): for IP20/IP40 protection rating, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, standard: EN 60598, packaging unit: 1 piece



Wt. (kg): 4.0

GTIN (EAN): 4039806496287





Order No.: 5TR10270Q | GTIN (EAN): 4039806496287

Detailed technical description: Mod,trunk.rail,2lg,L2990,7x2.52,wh

Key data

 Product type: trunking components group (TS)

Product name: Modario®Order No.: 5TR10270Q

Lighting technology | Lamps | Control gear

Component 1

Lamps:

 Supplement: for electrical and mechanical plug and socket connection of rail elements

Certificates, Standards

- Protection rating: for IP20/IP40 protection rating
- Insulation class: insulation class I (protective earthing)
- Standard: EN 60598
- Certification, designation: CE, ENEC, VDE

Material, Colour

- trunking rail: sheet steel, coated, pure white, 2-length
- Colour specification: pure white

Mounting

- Mounting method, mounting location: suspended mounting, surfacemounted, to the ceiling
- Arrangement: single/continuous arrangement
- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: terminal, 7-pole, max.
 2.5mm²
- Through-wiring: 7x 2.5mm²

Dimensions, Weight

System units: 10x SELength: 2990mmWidth: 58mmHeight: 43mm

- Mounting distance: max. 3.5m

- Weight: 4.0kg



Order No.: 5TR10270Q | **GTIN (EAN):** 4039806496287

Dimensions: Mod,trunk.rail,2lg,L2990,7x2.52,wh

