

Order No.: 51MP26WD2441E | **GTIN (EAN):** 4058352614631

Product description: Apol31Sf,1545x200,4600lm840,DA2



Apollon® 31 Surface, office luminaire, primary optical cover: micro prismatic cover, of PMMA, light emission: direct distribution, primary light characteristic: symmetric, installation type: surface-mounted, LED, rated luminous flux: 4.600lm, luminous efficacy: 139lm/W, light colour: 840, colour temperature: 4000K, control gear: DALI 2, with terminal, 5-pole, mains connection: 220..240V, AC, 50/60Hz, rated input power: 33W, housing, of sheet steel, coil coated, metallic grey (RAL 9006), length: 1.545mm, width: 200mm, height: 44mm, protection rating (complete): IP40, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, UKCA, impact resistance: IK02, permissible operating ambient temperature: -20..+40°C, standard: EN 60598-2-22, packaging unit: 1 piece

 IP 40  

Lamps:	LED
Wt. (kg):	4.1
GTIN (EAN):	4058352614631

Order No.: 51MP26WD2441E | **GTIN (EAN):** 4058352614631

Detailed technical description: Apol31Sf,1545x200,4600lm840,DA2



Key data

- Product type: office luminaire
- Product name: Apollon® 31 Surface
- Order No.: 51MP26WD2441E

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: micro prismatic cover
- Beam angle: wide distribution, 90°
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis: ≤ 19
- UGR viewing direction along lateral luminaire axis: ≤ 19

Lamps:

- Lamps: with LED
- Rated luminous flux: 4600lm
- Luminous efficacy: 139lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 33W
- Supplement: with through-wiring, maximum luminous flux 7400lm (UGR22)

Operating device:

- Control: DALI 2

Certificates, Standards

- Protection rating: IP40
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK02
- Temperature range (operation): -20...+40°C
- Standard: EN 60598-2-22
- Certification, designation: CE, ENEC, UKCA

Material, Colour

- housing: sheet steel, coil coated, metallic grey (RAL 9006)
- Colour specification: metallic grey (RAL 9006)
- Cover: micro prismatic cover of PMMA

Mounting

- Mounting method, mounting location: surface-mounted, to the ceiling
- Arrangement: single arrangement

Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 220...240V, 50/60Hz, AC

Dimensions, Weight

- Length: 1545mm
- Width: 200mm
- Height: 44mm
- Weight: 4.1kg

Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 08.08.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -