

**Order No.:** 5DTAXTSF42003 | **GTIN (EAN):** 4050737913582

**Product description:** AXT,3ph-tr,rec,wh,L2000,0/1



AX T, 3-phase track, installation type: recessed, control gear: ON/OFF, mains connection: 220..240V/380..400V, AC, of extruded aluminium section, coated, white, can be cut to preference, length: 2.000mm, width: 32mm, height: 33mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, packaging unit: 1 piece

 IP 20  

Wt. (kg): 1.9  
GTIN (EAN): 4050737913582

Order No.: 5DTAXTSF42003 | GTIN (EAN): 4050737913582

Detailed technical description: AXT,3ph-tr,rec,wh,L2000,0/1



#### Key data

- Product type: 3-phase track
- Product name: AX T
- Order No.: 5DTAXTSF42003

#### Lighting technology | Lamps | Control gear

#### Component 1

##### Lamps:

- Supplement: max. 16A

##### Operating device:

- Control: ON/OFF

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE, ENEC

#### Mounting

- Mounting method, mounting location: recessed, in the ceiling

#### Electrical connection

- Nominal voltage: 220..240V/380..400V, AC

#### Dimensions, Weight

- Length: 2000mm
- Width: 32mm
- Height: 33mm
- Weight: 1.9kg