

Order No.: 5XA7671C0000C | **GTIN (EAN):** 4058352236420

Product description: FL20mn,hous,Basic,96W,IC1



Floodlight FL 20 mini, housing, primary light characteristic: asymmetric, control gear: Basic, control: overheat protection, power reduction, electronic power reduction, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, rated input power: 96W, housing frame, housing, of diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm, solid metal housing for good heat sinkage, length: 446mm, width: 355mm, height: 62mm, ON/OFF, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, standard: DIN EN 12944, packaging unit: 1 piece

IP 66  

Wt. (kg): 3.3
GTIN (EAN): 4058352236420

Order No.: 5XA7671C0000C | GTIN (EAN): 4058352236420

Detailed technical description: FL20mn,hous,Basic,96W,IC1



Key data

- Product type: housing
- Product name: Floodlight FL 20 mini
- Order No.: 5XA7671C0000C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Symmetry: asymmetric distribution

Lamps:

- Rated input power: 96W

Operating device:

- Control gear: ECG Basic
- Control: Basic
- Equipment: overheat protection, power reduction
- Switching method: electronic power reduction

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Standard: DIN EN 12944
- Certification, designation: CE

Material, Colour

- housing frame: diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- housing: diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm

Electrical connection

- Connection: terminal, 5-pole, max. 2.5mm²
- Nominal voltage: 220..240V, AC

Dimensions, Weight

- Length: 446mm
- Width: 355mm
- Height: 62mm
- Weight: 3.3kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 14.03.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -