

Order No.: 5XA7671B0000C | **GTIN (EAN):** 4058352236406

Product description: FL20mn,hous,Basic,51W,IC1



Floodlight FL 20 mini, housing, primary light characteristic: asymmetric, control gear: ECG Basic, control: power reduction, overheat protection, electronic power reduction, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, rated input power: 51W, housing frame, housing, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm, length: 446mm, width: 355mm, height: 62mm, ON/OFF, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, ENEC, VDE, standard: DIN EN 12944, packaging unit: 1 piece



Wt. (kg): 2.9
GTIN (EAN): 4058352236406

Order No.: 5XA7671B0000C | GTIN (EAN): 4058352236406

Detailed technical description: FL20mn,hous,Basic,51W,IC1



Key data

- Product type: housing
- Product name: Floodlight FL 20 mini
- Order No.: 5XA7671B0000C

Dimensions, Weight

- Length: 446mm
- Width: 355mm
- Height: 62mm
- Weight: 2.9kg

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Symmetry: asymmetric distribution

Lamps:

- Rated input power: 51W

Operating device:

- Control gear: ECG Basic
- Control: Basic
- Equipment: overheat protection, power reduction
- Switching method: electronic power reduction

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Standard: DIN EN 12944
- Certification, designation: CE, ENEC, VDE

Material, Colour

- housing frame: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- housing: diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- Colour specification: Siteco® metallic grey (DB 702S)

Electrical connection

- Connection: terminal, 5-pole, max. 2.5mm²
- Nominal voltage: 220..240V, AC
- Surge voltage resistance: 10kV 1.2/50µs

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 07.07.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -