


Order No.: 51SD34MBD5A | GTIN (EAN): 4058352716519 Product description: Spot11,45°,5670Im940,ML,105,bk

Spot 11, directional spotlight, light control with lens, of PMMA, LED rated luminous flux: 5.670lm, light colour: 940, control gear: ECG Multilumen, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, of aluminium, matt jet black (RAL 9005), length: 213mm, diameter: 105mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, permissible ambient temperature for indoor applications: -20..+40°C, packaging unit: 1 piece

IP 20 🔔 🤆

Lamps: LED Wt. (kg): 1.1 GTIN (EAN): 4058352716519



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 51SD34MBD5A | GTIN (EAN): 4058352716519 Detailed technical description: Spot11,45°,5670lm940,ML,105,bk

Key data

- Product type: directional spotlight
- Product name: Spot 11
- Order No.: 51SD34MBD5A

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of PMMA
- Beam angle: 45°
- Symmetry: symmetric
- UGR viewing direction along longitudinal luminaire axis: ≤ 16
- UGR viewing direction along lateral luminaire axis: ≤ 16

Lamps:

- Lamps: with LED
- Rated luminous flux: 5670lm
- Luminous efficacy: 149lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 90
- Light colour: 940
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 38W

Operating device:

- Control gear: ECG Multilumen
- Control: ON/OFF Multilumen

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Temperature range (operation): -20..+40°C
- Certification, designation: CE

Material, Colour

 Colour specification: matt jet black (RAL 9005)

Mounting

 Mounting method, mounting location: slip-in mounting, in a 3-phase track

Electrical connection

 Connection: 3-phase adapter
Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight


- Length: 213mm
- Diameter: 105mm
- Weight: 1.1kg

Service life

 Rated service life: 50000h (L80/B50) at AT = 25°C



Order No.: 51SD34MBD5A | **GTIN (EAN):** 4058352716519 **Dimensions:** Spot11,45°,5670lm940,ML,105,bk



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -