


**Order No.:** 51SD35MAD5A | **GTIN (EAN):** 4058352716540

**Product description:** Spot11,60°,5870lm940,ML,90,bk

Spot 11, directional spotlight, light control with lens, of PMMA, LED rated luminous flux: 5.870lm, light colour: 940, control gear: ECG Multilumen, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, of aluminium, matt jet black (RAL 9005), length: 213mm, diameter: 90mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, permissible ambient temperature for indoor applications: -20..+40°C, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	0.8
GTIN (EAN):	4058352716540



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 51SD35MAD5A | GTIN (EAN): 4058352716540

Detailed technical description: Spot11,60°,5870lm940,ML,90,bk

#### Key data

- Product type: directional spotlight
- Product name: Spot 11
- Order No.: 51SD35MAD5A

#### Electrical connection

- Connection: 3-phase adapter
- Nominal voltage: 220..240V, 50/60Hz, AC

#### Lighting technology | Lamps | Control gear

#### Dimensions, Weight

- Length: 213mm
- Diameter: 90mm
- Weight: 0.8kg

#### Component 1

#### Lighting technology:

- Light control: lens of PMMA
- Beam angle: 60°
- Symmetry: symmetric
- UGR viewing direction along longitudinal luminaire axis:  $\leq 16$
- UGR viewing direction along lateral luminaire axis:  $\leq 16$

#### Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 5870lm
- Luminous efficacy: 152lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 90
- Light colour: 940
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 3$  SDCM (initial)
- Rated input power: 38.5W

#### Operating device:

- Control gear: ECG Multilumen
- Control: ON/OFF Multilumen

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Temperature range (operation): -20..+40°C
- Certification, designation: CE

#### Material, Colour

- Colour specification: matt jet black (RAL 9005)

#### Mounting

- Mounting method, mounting location: slip-in mounting, in a 3-phase track

Order No.: 51SD35MAD5A | GTIN (EAN): 4058352716540

Dimensions: Spot11,60°,5870lm940,ML,90,bk

