

**Order No.:** 5EA3TDC01 | **GTIN (EAN):** 4058352812044

**Product description:** SConWi,SmartPlugCasambi



SITECO Connect WirelessSmart Plug Casambi, luminaire controller, communication: 2.4GHz, Bluetooth, local mesh radio network, D4i type A, control: local setting and operation with smartphone app, manual, by daylight, optionally via radio push button, sensor technology: daylight sensor, configuration via Casambi app, Compatible only with ECGs with logarithmic DALI dimming curve, Smart Interface below and above, installation type: screw fastening, installation location: to the luminaire, of PBT, voltage: 12..20V, protection rating (complete): IP66, certification: CE, UKCA, packaging unit: 1 piece

IP 66 IK 09

Wt. (kg): 0.1  
GTIN (EAN): 4058352812044

**Order No.:** 5EA3TDC01 | **GTIN (EAN):** 4058352812044

**Detailed technical description:** SConWi,SmartPlugCasambi



#### Key data

- System family: SITECO Connect 31 Wireless
- Product type: luminaire controller
- Product name: SITECO Connect Wireless
- Order No.: 5EA3TDC01

#### Lighting technology | Lamps | Control gear

#### Component 1

##### Operating device:

- Control: D4i, Casambi, Smart Interface below and above, configuration via Casambi app, Compatible only with ECGs with logarithmic DALI dimming curve

##### Certificates, Standards

- Protection rating: IP66
- Impact resistance: IK09
- Temperature range (operation): -40..+70°C
- Standard: according to Zhaga book 18
- Certification, designation: CE, UKCA

##### Material, Colour

- housing: PBT, transparent, colour-backed, transparent
- Colour specification: transparent

##### Mounting

- Mounting method, mounting location: screw fastening, to the luminaire

##### Electrical connection

- Nominal voltage: 12..20V

##### Dimensions, Weight

- Weight: 0.1kg