

Order No.: 51MR34ND0421S | **GTIN (EAN):** 4058352882504

Product description: Round21S, Prism, dir/ind, 3800lm840, DA2, sr








Round 21 S, wall and ceiling luminaire, primary optical cover: micro prismatic cover, of PMMA, transparent, CAT 2 (L≤ 3000cd/m²), light emission: direct/indirect distribution, primary light characteristic: symmetric, installation type: surface-mounted, suspended mounting, LED, rated luminous flux: 3.800lm, luminous efficacy: 135lm/W, light colour: 840, colour temperature: 4000K, control gear: DALI 2, with terminal, 5-pole, mains connection: 230V, AC, 50/60Hz, rated input power: 28.3W, housing, of aluminium, coated, silver, diameter: 400mm, height: 62mm, protection rating (complete): IP40, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK04, permissible operating ambient temperature: -10..+35°C, packaging unit: 1 piece

IP 40 (≟) (∈

Lamps: LED Wt. (kg): 3.9

GTIN (EAN): 4058352882504





Order No.: 51MR34ND0421S | GTIN (EAN): 4058352882504

Detailed technical description: Round21S, Prism, dir/ind, 3800lm840, DA2, sr



Key data

- Product type: wall and ceiling luminaire
- Product name: Round 21 S
- Order No.: 51MR34ND0421S

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: micro prismatic cover, transparent
- Beam angle: 85°
- Symmetry: symmetric
- Light emission: direct/indirect distribution
- UGR viewing direction along longitudinal luminaire axis: ≤ 19
- UGR viewing direction along lateral luminaire axis: ≤ 19

Lamps:

- Lamps: with LED
- Rated luminous flux: 3800lm
 Luminous efficacy: 135lm/W
 Colour temperature: 4000K
 Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 28.3W

Operating device:

- Control: DALI 2

Certificates, Standards

- Protection rating: IP40
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK04
- Temperature range (operation): -10..+35°C
- Certification, designation: CE

Material, Colour

- housing: aluminium, coated, silver
- Colour specification: silver
- Cover: micro prismatic cover of PMMA

Mounting

- Mounting method, mounting location: suspended mounting, surfacemounted, to the ceiling, to the wall
- Arrangement: single arrangement

Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 230V, 50/60Hz, AC

Dimensions, Weight

- Diameter: 400mmHeight: 62mm
- Weight: 3.9kg

Service life

 Rated service life: 50000h (L80/B20) at AT = 25°C



Order No.: 51MR34ND0421S | GTIN (EAN): 4058352882504

Dimensions: Round21S, Prism, dir/ind, 3800lm840, DA2, sr

