

Order No.: 51SL127A43B | **GTIN (EAN):** 4058352863428

Product description: LicSp31,21°,3650lm940,0/1,wh



Licross® Spot 31, directional spotlight, light control with lens, of plastic, LED rated luminous flux: 3.650lm, light colour: 940, with plug, 3-pole, with phase selection, mains connection: 220..240V, AC, 50/60Hz, of aluminium, traffic white (RAL 9016), length: 140mm, diameter: 90mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	1.2
GTIN (EAN):	4058352863428



Order No.: 51SL127A43B | GTIN (EAN): 4058352863428

Detailed technical description: LicSp31,21°,3650lm940,0/1,wh



Key data

- Product type: directional spotlight
- Product name: Licross® Spot 31
- Order No.: 51SL127A43B

Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of plastic
- Beam angle: 21°
- Symmetry: symmetric

Lamps:

- Lamps: with LED
- Rated luminous flux: 3650lm
- Colour temperature: 4000K
- Colour rendering index: CRI > 90
- Light colour: 940
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 28W

Operating device:

- Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- Colour specification: traffic white (RAL 9016)

Mounting

- Mounting method, mounting location: slip-in mounting, in the Licross® trunking rail

Electrical connection


- Connection: plug, 3-pole, with phase selection
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 140mm
- Diameter: 90mm
- Height: 116mm
- Weight: 1.2kg

Order No.: 51SL127A43B | GTIN (EAN): 4058352863428

Dimensions: LicSp31,21°,3650lm940,0/1,wh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -