

Order No.: 51SL347A45B | GTIN (EAN): 4058352865187

Product description: LicSp31,40°,5250lm940,0/1,bk



Licross® Spot 31, directional spotlight, light control with lens, of plastic, LED rated luminous flux: 5.250lm, light colour: 940, control gear: ECG, with plug, 3-pole, with phase selection, mains connection: 220..240V, AC, 50/60Hz, of aluminium, jet black (RAL 9005), length: 140mm, diameter: 90mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	1.2
GTIN (EAN):	4058352865187



Order No.: 51SL347A45B | GTIN (EAN): 4058352865187

Detailed technical description: LicSp31,40°,5250lm940,0/1,bk



Key data

- Product type: directional spotlight
- Product name: Licross® Spot 31
- Order No.: 51SL347A45B

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of plastic
- Beam angle: 40°
- Symmetry: symmetric

Lamps:

- Lamps: with LED
- Rated luminous flux: 5250lm
- Colour temperature: 4000K
- Colour rendering index: CRI > 90
- Light colour: 940
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 42.4W

Operating device:

- Control gear: ECG
- Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- Colour specification: jet black (RAL 9005)

Mounting

- Mounting method, mounting location: slip-in mounting, in the Licross® trunking rail

Electrical connection

- Connection: plug, 3-pole, with phase selection
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 140mm
- Diameter: 90mm
- Height: 116mm
- Weight: 1.2kg

Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Order No.: 51SL347A45B | GTIN (EAN): 4058352865187

Dimensions: LicSp31,40°,5250lm940,0/1,bk



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 08.09.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -