

Order No.: 5EA40RS01 | GTIN (EAN): 4058352916476


Product description: SConWi,MotionRadar



SITECO Connect Wireless Motion Radar, Smart Interface below, installation type: screw fastening, installation location: to the luminaire, of plastic, voltage: 24V, voltage type: DC, D4i, local setting and operation with USB stick, by movement, 2 radar movement sensors, radar movement sensor, radio, 2.4GHz, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 IK 09 CE

Wt. (kg): 0.1  
GTIN (EAN): 4058352916476



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 22.12.2023 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5EA40RS01 | GTIN (EAN): 4058352916476

Detailed technical description: SConWi,MotionRadar



#### Key data

- Product type: sensor
- Product name: SITECO Connect Wireless
- Order No.: 5EA40RS01

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Operating device:

- Control: D4i, Smart Interface below

#### Certificates, Standards

- Protection rating: IP66
- Impact resistance: IK09
- Temperature range (operation): -20..+60°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

#### Material, Colour

- housing: plastic, transparent, colour-backed, black
- Colour specification: black

#### Mounting

- Mounting method, mounting location: screw fastening, to the luminaire
- Mounting height: 4..8m

#### Electrical connection

- Nominal voltage: 24V, DC

#### Dimensions, Weight

- Diameter: 80mm
- Height: 63mm
- Weight: 0.1kg

#### Inputs

#### radar movement sensor

- Detection range: max. 70x20m

Mounting height 5m

X axis

Y axis

Vehicles

70.0 m

15.0 m

People

25.0 m

10.0 m

**Dimensions: SConWi, MotionRadar**

