

## Order No.: 5XMOD1125M | GTIN (EAN): 4058352780695 Product description: SL10mnmd,LEDmod,PCL,722




Streetlight 10 mini/midi, LED module, primary light control with pedestrian crossing, asymmetric left distribution, light distribution: PC-L, High Power LED, light colour: 722, colour temperature: 2200K, mains connection: 230..240V, 50Hz, LED module, length: 310mm, width: 137mm, height: 40mm, protection rating (complete): as luminaire, packaging unit: 1 piece

Wt. (kg): 1.2 GTIN (EAN): 4058352780695

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 17.02.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

# ѕітесо

## Order No.: 5XMOD1125M | GTIN (EAN): 4058352780695 Detailed technical description: SL10mnmd,LEDmod,PCL,722



#### Key data

- Product type: LED module
- Product name: Streetlight 10 mini/midi
- Order No.: 5XMOD1125M

# Lighting technology | Lamps | Control gear

#### **Component 1**

#### Lighting technology:

- Light control: pedestrian crossing, asymmetric left distribution
- Light distribution: PC-L

#### Lamps:

- Lamps: with High Power LED
- Colour temperature: 2200K
- Colour rendering index: CRI > 70
- Light colour: 722
- Supplement: power consumption when used in Streetlight 10 Plus luminaires: construction size mini 18.5..26.0W, construction size midi 51.9..73.5W

#### **Certificates, Standards**

- Protection rating: as luminaire

#### **Electrical connection**

- Nominal voltage: 230..240V, 50Hz

#### **Dimensions, Weight**

- Length: 310mm
- Width: 137mm
- Height: 40mm
- Weight: 1.2kg