

Order No.: 51MQ11WD2414M | **GTIN (EAN):** 4058352928127


Product description: Apollon[®] 21s, M625, 4200lm, 840, DA2, IP50, 5pcs



Apollon[®] 21 square, office luminaire, primary optical cover: micro prismatic cover, of PMMA, CAT 2 ($L \leq 3000 \text{cd/m}^2$), light emission: direct distribution, primary light characteristic: symmetric, installation type: lay-in mounting, LED, rated luminous flux: 4.200lm, luminous efficacy: 170lm/W, light colour: 840, colour temperature: 4000K, with terminal, 5-pole, mains connection: 220..240V, AC/DC, 0/50..60Hz, rated input power: 24.7W, housing, of aluminium, coated, traffic white (RAL 9016), module: M625, length: 620mm, width: 620mm, height: 30mm, housing upper side, of sheet steel, galvanised, protection rating (complete): IP20, protection rating (lamp compartment, on room side): IP50, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, impact resistance: IK03, permissible operating ambient temperature: -20..+45°C, permissible storage temperature: -40..+80°C, packaging unit: set of 5



Lamps:	LED
Wt. (kg):	10.7
GTIN (EAN):	4058352928127



Order No.: 51MQ11WD2414M | **GTIN (EAN):** 4058352928127

Detailed technical description: Apol21s,M625,4200lm840,DA2,IP50,5pcs



Key data

- Product type: office luminaire
- Product name: Apollon® 21 square
- Order No.: 51MQ11WD2414M

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: micro prismatic cover
- Beam angle: wide distribution, 90°
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis: ≤ 19
- UGR viewing direction along lateral luminaire axis: ≤ 19

Lamps:

- Lamps: with LED
- Rated luminous flux: 4200lm
- Luminous efficacy: 170lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 24.7W

Operating device:

- Control: DALI 2

Certificates, Standards

- Protection rating: IP20
- Protection rating (lamp compartment, on room side): IP50
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK03
- Temperature range (operation): -20..+45°C
- Certification, designation: CE, ENEC

Material, Colour

- housing: aluminium, coated, traffic white (RAL 9016)
- Colour specification: traffic white (RAL 9016)
- housing upper side: sheet steel, galvanised
- Cover: micro prismatic cover of PMMA

Mounting

- Mounting method, mounting location: lay-in mounting, in the ceiling
- Arrangement: single arrangement

Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 220..240V, 0/50..60Hz, AC/DC

Dimensions, Weight

- Length: 620mm
- Width: 620mm
- Height: 30mm
- Weight: 10.7kg

Service life

- Rated service life: 100000h (L80/B50) at AT = 25°C, 50000h (L90/B50) at AT = 25°C

Order No.: 51MQ11WD2414M | GTIN (EAN): 4058352928127

Dimensions: Apol21s,M625,4200lm840,DA2,IP50,5pcs

