

Order No.: 5EA3NAS01 | GTIN (EAN): 4058352812969 Product description: SConWi,SmartPlugLoRaWAN



SITECO Connect WirelessSmart Plug LoRaWAN, luminaire controller, communication: LoRaWAN, D4i type A, control: remote setup and operation, local setting and operation with smartphone app, The LoRaWAN key is included in the individual packaging, Smart Interface below and above, installation type: screw fastening, installation location: to the luminaire, of ABS, voltage: 12..20V, voltage type: DC, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 (E

Wt. (kg): 0.1 GTIN (EAN): 4058352812969

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com) Tolerances related to thermal, electrical and photometric data according to IEC 62722 Issued 10.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

ѕітесо

Order No.: 5EA3NAS01 | GTIN (EAN): 4058352812969 Detailed technical description: SConWi,SmartPlugLoRaWAN



Key data

- System family: SITECO Connect 31 Wireless
- Product type: luminaire controller
- Product name: SITECO Connect Wireless
- Order No.: 5EA3NAS01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

 Control: D4i, Smart Interface below and above, The LoRaWAN key is included in the individual packaging

Certificates, Standards

- Protection rating: IP66
- Temperature range (operation): -30..+60°C
- Standard: according to Zhaga book 18
- Certification, designation: CE

Material, Colour

- housing: ABS, grey
- Colour specification: grey

Mounting

 Mounting method, mounting location: screw fastening, to the luminaire

Electrical connection

- Nominal voltage: 12..20V, DC

Dimensions, Weight

Weight: 0.1kg