

**Order No.:** 59LN201 | **GTIN (EAN):** 4058352062234

**Product description:** SIU21multisens, HFsens, surf



Siluette 21, multi-sensor, installation type: surface-mounted, mains connection: 220..240V, 50/60Hz, housing, length: 149mm, height: 28mm, multi-sensor, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, permissible operating ambient temperature: -20..+60°C, packaging unit: 1 piece

IP 20  CE

Wt. (kg): 0.1  
GTIN (EAN): 4058352062234

**Order No.:** 59LN201 | **GTIN (EAN):** 4058352062234

**Detailed technical description:** SIU21multisens, HFsens, surf

#### **Key data**

- Product type: multi-sensor
- Product name: Siluette 21
- Order No.: 59LN201

#### **Certificates, Standards**

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): - 20..+60°C
- Certification, designation: CE

#### **Mounting**

- Mounting method, mounting location: surface-mounted, to the luminaire
- Mounting height: 3m

#### **Electrical connection**

- Nominal voltage: 220..240V, 50/60Hz

#### **Dimensions, Weight**

- Length: 149mm
- Height: 28mm
- Weight: 0.1kg

#### **Inputs**

##### **1x HF sensor**

- Connection: HF sensor
- Detection range: ø10m
- Option: switching time adjustable between 5 seconds - 30 minutes
- Feature: for motion detection

##### **1x light sensor**

- Connection: light sensor
- Option: daylight threshold adjustable from 2..50lx

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))  
Tolerances related to thermal, electrical and photometric data according to IEC 62722  
Issued 30.10.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -