

Order No.: 5WD7A8P0G2C5 | **GTIN (EAN):** 4069025065506


Product description: TLL,LI,op840,DA,wh



TL L, luminaire insert, of sheet steel, galvanised, coil coated, white, length: 1.500mm, width: 66mm, height: 67mm, surge protection, LED light colour: 840, control gear: DALI, with terminal, 5-pole, mains connection: 230..240V, AC, 50/60Hz, rated input power: 30W, primary optical cover: cover, of PMMA, light emission: direct distribution, protection rating (complete): as luminaire, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK06, permissible ambient temperature for indoor applications: -35..+35°C, standard: NMF01, packaging unit: 1 piece

IK 06  

Lamps:	LED
Wt. (kg):	1.0
GTIN (EAN):	4069025065506



Order No.: 5WD7A8P0G2C5 | GTIN (EAN): 4069025065506

Detailed technical description: TLL,LI,op840,DA,wh



Key data

- Product type: luminaire insert
- Product name: TL L
- Order No.: 5WD7A8P0G2C5

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: cover
- Beam angle: open distribution
- Light emission: direct distribution

Lamps:

- Lamps: with LED
- Luminous efficacy: 166lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- SDCM (Standard Deviation of Colour Matching): MacAdam \leq 3 SDCM (initial)
- Rated input power: 30W

Operating device:

- Control: DALI

Certificates, Standards

- Protection rating: as luminaire
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK06
- Temperature range (operation): -35..+35°C
- Standard: NMF01
- Certification, designation: CE

Material, Colour

- luminaire insert LED: sheet steel, galvanised, coil coated, white
- Colour specification: white
- Cover: cover of PMMA

Mounting

- Mounting method, mounting location: recessed, in existing luminaire
- Supplement: mounting accessories required, please order separately

Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 230..240V, 50/60Hz, AC

Dimensions, Weight


- Length: 1500mm
- Width: 66mm
- Height: 67mm
- Weight: 1.0kg

Service life

- Rated service life: 100000h (L90/B10) at AT = 25°C

Order No.: 5WD7A8P0G2C5 | GTIN (EAN): 4069025065506

Dimensions: TLL,LI,op840,DA,wh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 12.04.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -