

**Order No.:** 51MX6MTST4W | **GTIN (EAN):** 4069025006547


**Product description:** Sil21sq,ELD-Lwh,3720lm8tw,DT8,M600,wh,li



Silica® 21 Square, office luminaire, primary light control with lens, of PMMA, primary anti-glare with reflector, of PC, white, CAT 2 ( $L \leq 3000 \text{cd/m}^2$ ), light emission: direct distribution, primary light characteristic: symmetric, installation type: lay-in mounting, LED, rated luminous flux: 3.720lm, luminous efficacy: 113lm/W, light colour: 8tw, colour temperature: 2700..6500K, with terminal, 5-pole, mains connection: 220..240V, AC, 50/60Hz, rated input power: 32.8W, luminaire housing, of aluminium, traffic white (RAL 9016), module: M600, length: 600mm, width: 600mm, height: 32mm, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, permissible operating ambient temperature: 0..+35°C, standard: EN 50419, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	4.5
GTIN (EAN):	4069025006547



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 08.05.2024 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 51MX6MTST4W | **GTIN (EAN):** 4069025006547

**Detailed technical description:** Sil21sq,ELD-Lwh,3720lm8tw,DT8,M600,wh,li



#### Key data

- Product type: office luminaire
- Product name: Silica® 21 Square
- Order No.: 51MX6MTST4W

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lighting technology:

- Light control: lens of PMMA
- Glare reduction: reflector of PC, white
- Beam angle: wide distribution
- Symmetry: symmetric
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis:  $\leq 19$
- UGR viewing direction along lateral luminaire axis:  $\leq 19$

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 3720lm
- Luminous efficacy: 113lm/W
- Colour temperature: 2700..6500K
- Colour rendering index: CRI > 80
- Light colour: 8tw
- SDCM (Standard Deviation of Colour Matching): MacAdam  $\leq 3$  SDCM (initial)
- Rated input power: 32.8W

#### Operating device:

- Control: DALI-2 DT8

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0..+35°C
- Standard: EN 50419
- Certification, designation: CE

#### Material, Colour

- luminaire housing: aluminium, traffic white (RAL 9016)
- Colour specification: traffic white (RAL 9016)

#### Mounting

- Mounting method, mounting location: lay-in mounting, in the ceiling
- Arrangement: single arrangement

#### Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 220..240V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 600mm
- Width: 600mm
- Height: 32mm
- Weight: 4.5kg

#### Service life

- Rated service life: 50000h (L85/B50) at AT = 25°C

Order No.: 51MX6MTST4W | GTIN (EAN): 4069025006547

Dimensions: Sil21sq,ELD-Lwh,3720lm8tw,DT8,M600,wh,li

