

Order No.: 5XA7661A0000C | **GTIN (EAN):** 4058352230534

Product description: FL20mc,hous,Basic,27W,IC1



Floodlight FL 20 micro, housing, primary light characteristic: asymmetric, control gear: Basic, mains connection: 220..240V, AC, rated input power: 27W, housing frame, housing, of diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm, solid metal housing for good heat sinkage, length: 304mm, width: 222mm, height: 55mm, ON/OFF, protection rating (complete): IP66, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece

IP 66  

Wt. (kg): 1.6
GTIN (EAN): 4058352230534

Order No.: 5XA7661A0000C | **GTIN (EAN):** 4058352230534

Detailed technical description: FL20mc,hous,Basic,27W,IC1



Key data

- Product type: housing
- Product name: Floodlight FL 20 micro
- Order No.: 5XA7661A0000C

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Symmetry: asymmetric distribution

Lamps:

- Rated input power: 27W

Operating device:

- Control gear: ECG Basic
- Control: Basic

Certificates, Standards

- Protection rating: IP66
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

Material, Colour

- housing frame: diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm
- housing: diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), incl. 1x M20 cable gland for cable Ø 6.5..12mm

Electrical connection

- Nominal voltage: 220..240V, AC

Dimensions, Weight

- Length: 304mm
- Width: 222mm
- Height: 55mm
- Weight: 1.6kg