

Order No.: 5XA1575E1F | **GTIN (EAN):** 4069025073846

Product description: GT,S120005,3220lm730,SR,asy,SmBelliQ



Small Bell iQ, electrics components group, gear tray, primary light control with 3 zone faceted reflector, of plastic, silver coated, light distribution: S120005, primary beam angle: wide distribution, primary light characteristic: asymmetric, rated values: 3.220lm | 20,1W | 160,2lm/W (begin service life); end service life: 3.220lm | 20,6W; at 50% lumin. flux: 1.610lm | 9,9W | 162,6lm/W, colour temperature: 3000K, colour rendering: CRI > 70, light colour: 730, light setting 1 (further light settings possible): 100% | 3.220lm | 20,1W | 160,2lm/W | 3.000K (begin service life); end service life: 20,6W, control gear: iQ Street-Remote, control: pre-setting: logarithmic dimming characteristic, Street-Remote, Auto-Match, Temp-Guard, Lumen-Switch, Night-Set, Smart-Wire, Light-Fading, Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), optimised constant luminous flux control (CLO 2.0), pre-setting: linear dimming characteristic, mains connection: 220..240V, AC, 50/60Hz, surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode), gear tray, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, packaging unit: 1 piece



Wt. (kg): 1.6
GTIN (EAN): 4069025073846

Order No.: 5XA1575E1F | **GTIN (EAN):** 4069025073846

Detailed technical description: GT,S120005,3220lm730,SR,asy,SmBelliQ



Key data

- Product type: electrics components group
- Product name: Small Bell iQ
- Order No.: 5XA1575E1F

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: 3 zone faceted reflector of plastic, silver coated
- Light distribution: S120005
- Beam angle: wide distribution
- Symmetry: asymmetric distribution

Lamps:

- Rated values: 3220lm | 20.1W | 160.2lm/W (begin service life); end service life: 3220lm | 20.6W; at 50% lumin. flux: 1610lm | 9.9W | 162.6lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 70
- Light colour: 730

Factory light settings (LS):

- begin service life:
LS 1: 100% | 3220lm | 20.1W | 160.2lm/W | 3000K
- end service life:
LS 1: 20.6W
- further light settings possible

Operating device:

- Control: iQ Street-Remote
- Equipment: optimised constant luminous flux control (CLO 2.0), Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), Light-Fading, Smart-Wire, Night-Set, Lumen-Switch, Temp-Guard, Auto-Match, Street-Remote, pre-setting: logarithmic dimming characteristic, pre-setting: linear dimming characteristic

Certificates, Standards

- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE, ENEC, VDE

Electrical connection

- Nominal voltage: 220..240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)

Dimensions, Weight

- Weight: 1.6kg

Light emission

- Light emission: < 3%