

Order No.: 5XA1565E1F1 | **GTIN (EAN):** 4069025073730

Product description: GT,S120009,5180lm730,SR,asy,encl,PMMA



Large Bell iQ, electrics components group, gear tray with cover, primary light control with 3 zone faceted reflector, of plastic, silver coated, primary optical cover: enclosure, of PMMA, transparent, light distribution: S120009, primary beam angle: wide distribution, primary light characteristic: asymmetric, lamps: LED, rated values: 5.180lm | 34,3W | 151lm/W (begin service life); end service life: 5.180lm | 37,7W; at 50% lumin. flux: 2.590lm | 15,5W | 167,1lm/W, colour temperature: 3000K, colour rendering: CRI > 70, light colour: 730, light setting 1 (further light settings possible): 100% | 5.180lm | 34,3W | 151lm/W | 3.000K (begin service life); end service life: 37,7W, control gear: iQ Street-Remote, control: pre-setting: logarithmic dimming characteristic, Street-Remote, Auto-Match, Temp-Guard, Lumen-Switch, Night-Set, Smart-Wire, Light-Fading, Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), optimised constant luminous flux control (CLO 2.0), pre-setting: linear dimming characteristic, mains connection: 220..240V, AC, 50/60Hz, surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode), gear tray with cover, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, packaging unit: 1 piece



Lamps:	LED
Wt. (kg):	2.9
GTIN (EAN):	4069025073730

Order No.: 5XA1565E1F1 | **GTIN (EAN):** 4069025073730

Detailed technical description: GT,S120009,5180lm730,SR,asy,encl,PMMA



Key data

- Product type: electrics components group
- Product name: Large Bell iQ
- Order No.: 5XA1565E1F1

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: 3 zone faceted reflector of plastic, silver coated
- Cover: enclosure, transparent
- Light distribution: S120009
- Beam angle: wide distribution
- Symmetry: asymmetric distribution

Lamps:

- Lamps: with LED
- Rated values: 5180lm | 34.3W | 151lm/W (begin service life); end service life: 5180lm | 37.7W; at 50% lumin. flux: 2590lm | 15.5W | 167.1lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 70
- Light colour: 730

Factory light settings (LS):

- begin service life:
LS 1: 100% | 5180lm | 34.3W | 151lm/W | 3000K
- end service life:
LS 1: 37.7W
- further light settings possible

Operating device:

- Control: iQ Street-Remote
- Equipment: optimised constant luminous flux control (CLO 2.0), Desk-Remote (wireless, voltage-free reading and setting of iQ features in the workshop via application-optimized NFC function/RFID function), Light-Fading, Smart-Wire, Night-Set, Lumen-Switch, Temp-Guard, Auto-Match, Street-Remote, pre-setting: logarithmic dimming characteristic, pre-setting: linear dimming characteristic

Certificates, Standards

- Insulation class: insulation class II (safety insulation)
- Certification, designation: CE, ENEC, VDE

Material, Colour

- Cover: enclosure of PMMA

Electrical connection

- Nominal voltage: 220..240V, 50/60Hz, AC
- Surge voltage resistance: surge voltage resistance: 10kV (common mode); 6kV (differential mode)

Dimensions, Weight

- Weight: 2.9kg

Light emission

- Light emission: < 3%