

**Order No.:** 5XA769LEDUNITN1 | **GTIN (EAN):** 4069025289674

**Product description:** FL20mx,LED-unit,PL44TBLC,730



Floodlight FL 20 maxi, LED unit, primary light control with lens, of PMMA, primary optical cover: cover panel, of toughened safety glass, transparent, light distribution: PL44T Backlight Control, light emission: direct distribution, primary light characteristic: asymmetric, installation type: screw fastening, LED, High Power LED, light colour: 730, colour temperature: 3000K, with cable with plug, AC, 50/60Hz, LED unit, of diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), solid metal housing for good heat sinkage, length: 662mm, width: 298mm, height: 106mm, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66 CE

|             |               |
|-------------|---------------|
| Lamps:      | LED           |
| Wt. (kg):   | 6.4           |
| GTIN (EAN): | 4069025289674 |

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 14.03.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

**Order No.:** 5XA769LEDUNITN1 | **GTIN (EAN):** 4069025289674

**Detailed technical description:** FL20mx,LED-unit,PL44TBLC,730



## Key data

- Product type: LED unit
- Product name: Floodlight FL 20 maxi
- Order No.: 5XA769LEDUNITN1

## Lighting technology | Lamps | Control gear

### Component 1

#### Lighting technology:

- Light control: lens of PMMA
- Cover: cover panel, transparent
- Light distribution: PL44T Backlight Control
- Symmetry: asymmetric distribution
- Light emission: direct distribution

#### Lamps:

- Lamps: High Power LED, LED
- Colour temperature: 3000K
- Colour rendering index: CRI > 70
- Light colour: 730

#### Certificates, Standards

- Protection rating: IP66
- Certification, designation: CE

#### Material, Colour

- LED unit: diecast aluminium, powder-coated, SITECO metallic grey (DB 702S)
- Cover: cover panel of toughened safety glass

#### Mounting

- Mounting method, mounting location: screw fastening, in housing

#### Electrical connection

- Connection: cable with plug

#### Dimensions, Weight

- Length: 662mm
- Width: 298mm
- Height: 106mm
- Weight: 6.4kg