

Order No.: 5XA769LEDUNITQ1 | **GTIN (EAN):** 4069025289803

Product description: FL20mx,LED-unit,PL43K,730,chlor.resist



Floodlight FL 20 maxi, LED unit, primary light control with lens, of PMMA, primary optical cover: cover panel, of toughened safety glass, transparent, light distribution: PL43K, light emission: direct distribution, primary light characteristic: asymmetric, installation type: screw fastening, LED, High Power LED, light colour: 730, colour temperature: 3000K, with cable with plug, AC, 50/60Hz, LED unit, of diecast aluminium, powder-coated, SITECO metallic grey (DB 702S), solid metal housing for good heat sinkage, length: 662mm, width: 298mm, height: 106mm, protection rating (complete): IP66, certification: CE, packaging unit: 1 piece

IP 66



Lamps:	LED
Wt. (kg):	6.4
GTIN (EAN):	4069025289803

Order No.: 5XA769LEDUNITQ1 | **GTIN (EAN):** 4069025289803

Detailed technical description: FL20mx,LED-unit,PL43K,730,chlor.resist



Key data

- Product type: LED unit
- Product name: Floodlight FL 20 maxi
- Order No.: 5XA769LEDUNITQ1

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of PMMA
- Cover: cover panel, transparent
- Light distribution: PL43K
- Symmetry: asymmetric distribution
- Light emission: direct distribution

Lamps:

- Lamps: High Power LED, LED
- Colour temperature: 3000K
- Colour rendering index: CRI > 70
- Light colour: 730

Certificates, Standards

- Protection rating: IP66
- Certification, designation: CE

Material, Colour

- LED unit: diecast aluminium, powder-coated, SITECO metallic grey (DB 702S)
- Cover: cover panel of toughened safety glass

Mounting

- Mounting method, mounting location: screw fastening, in housing

Electrical connection

- Connection: cable with plug

Dimensions, Weight

- Length: 662mm
- Width: 298mm
- Height: 106mm
- Weight: 6.4kg