

**Order No.:** 5TR30000U | **GTIN (EAN):** 4069025325013

**Product description:** Mod,bl-ins,steel,wh,8su



Modario®, blank insert, of steel, coil coated, white, end cap, of ABS, transparent, length: 2.392mm, width: 48mm, 8x system unit, for industrial facilities, laboratory/development/technical college, storage/logistics, installation/production/process, manufacturing halls and storehouses, special areas/ancillary areas, protection rating (complete): for IP20 protection rating, insulation class (complete): insulation class I (protective earthing), certification: CE, packaging unit: 1 piece



Wt. (kg): 1.0  
GTIN (EAN): 4069025325013

**Order No.:** 5TR30000U | **GTIN (EAN):** 4069025325013

**Detailed technical description:** Mod,bl-ins,steel,wh,8su



#### Key data

- Product type: blank insert
- Product name: Modario®
- Order No.: 5TR30000U

#### Certificates, Standards

- Protection rating: for IP20 protection rating
- Insulation class: insulation class I (protective earthing)
- Certification, designation: CE

#### Material, Colour

- blank insert: steel, coil coated, white, 8x system unit
- Colour specification: white
- end cap: ABS, transparent
- Colour specification: transparent

#### Dimensions, Weight

- System units: 8x SE
- Length: 2392mm
- Width: 48mm
- Weight: 1.0kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 10.05.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -