


Order No.: 58DC011M04400A | **GTIN (EAN):** 4069025314178

Product description: LunR,LI,wd,4310lm840,ML



Lunis R, luminaire insert, rated luminous flux: 4.310lm, light colour: 840, control gear: ON/OFF Multilumen, mains connection: 220..240V, AC, 50/60Hz, rated input power: 25.9W, primary light control with lens, of plastic, primary optical cover: cover, of PMMA, light emission: direct distribution, protection rating (complete): IP20, certification: CE, packaging unit: 1 piece

IP 20 

Wt. (kg): 0.5
GTIN (EAN): 4069025314178

Order No.: 58DC011M04400A | GTIN (EAN): 4069025314178

Detailed technical description: LunR,LI,wd,4310lm840,ML



Key data

- Product type: luminaire insert
- Product name: Lunis R
- Order No.: 58DC011M04400A

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: lens of plastic
- Cover: cover
- Beam angle: wide distribution
- Light emission: direct distribution

Lamps:

- Rated luminous flux: 4310lm
- Luminous efficacy: 166lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- Rated input power: 25.9W

Operating device:

- Control: ON/OFF Multilumen

Certificates, Standards

- Protection rating: IP20
- Certification, designation: CE

Material, Colour

- Quantity: 1 piece
- Cover: cover of PMMA

Mounting

- Arrangement: single arrangement

Electrical connection

- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Weight: 0.5kg