

Order No.: 51MX52DA3ZM00891XX | **GTIN (EAN):** 4069025333674


Product description: Sil21FLL,14320lm830,DA2,PIR-sens,bk



Silica 21 Floor L, floorstanding luminaire, primary light control with darklight reflector, of PMMA, of PMMA, CAT 2 ($L \leq 3000\text{cd/m}^2$), light emission: indirect/direct distribution, primary light characteristic: symmetric, primary optical cover: cover panel, installation type: not mounted, LED, rated luminous flux: 14.320lm, luminous efficacy: 154lm/W, light colour: 830, colour temperature: 3000K, control gear: DALI 2, daylight-dependent control, mains connection: 230V, AC, 50/60Hz, connection cable pre-assembled, cable length: 2,5m, luminaire head, of aluminium, powder-coated, jet black (RAL 9005), length: 1.454mm, width: 280mm, height: 2190mm, supporting column, angular, of aluminium, powder-coated, jet black (RAL 9005), baseplate, of steel, powder-coated, jet black (RAL 9005), sensor module PR3-S, local control - self-sufficient standalone sensors, equipment: master, direct and indirect component separately switchable, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, permissible operating ambient temperature: 0..+35°C, standard: EN 50419, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	13.8
GTIN (EAN):	4069025333674




It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 17.08.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 51MX52DA3ZM00891XX | **GTIN (EAN):** 4069025333674

Detailed technical description: Sil21FLL,14320lm830,DA2,PIR-sens,bk



Key data

- Product type: floorstanding luminaire
- Product name: Silica 21 Floor L
- Order No.: 51MX52DA3ZM00891XX

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Cover: cover panel
- Beam angle: wide distribution

Lamps:

- Lamps: with LED
- Rated luminous flux: 14320lm
- Luminous efficacy: 154lm/W
- Colour temperature: 3000K
- Colour rendering index: CRI > 80
- Light colour: 830
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 93.2W
- Supplement: with ambient light and presence detector

Operating device:

- Control: DALI 2, direct and indirect component separately switchable
- Switching method: daylight-dependent control

Component 2

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Temperature range (operation): 0..+35°C
- Standard: EN 50419
- Certification, designation: CE

Material, Colour

- luminaire head: aluminium, powder-coated, jet black (RAL 9005)
- supporting column: aluminium, powder-coated, jet black (RAL 9005), angular
- Quantity: 1 piece
- baseplate: steel, powder-coated, jet black (RAL 9005)
- Quantity: 1 piece
- Cover: cover panel

Mounting

- Mounting method, mounting location: not mounted

Electrical connection

- Nominal voltage: 230V, 50/60Hz, AC
- Connection cable: pre-assembled, L= 2.5m

Dimensions, Weight

- Length: 1454mm
- Width: 280mm
- Height: 2190mm
- Weight: 13.8kg

Service life

- Rated service life: 50000h (L85) at AT = 25°C

Inputs

1x PIR movement sensor

- Connection: PIR sensor (passive-infrared)
- Detection angle: 360°
- Detection range: tangential max. 4x4m
- Detection range: max. 2x 2m
- Option: detection range can be limited in stages using extendable lens covers (2x 180°)
- Feature: rectangular detection area

1x light sensor

- Illuminance: 20..800lx (directly at sensor)

1x push button

- Connection: IR receiver
- Option: ON/OFF, dimming, setpoint storage separately for direct and indirect component

Outputs

1x LED red/green

- Feature: for displaying initialization


It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 17.08.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 51MX52DA3ZM00891XX | **GTIN (EAN):** 4069025333674

Dimensions: Sil21FLL,14320lm830,DA2,PIR-sens,bk



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 17.08.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -