siteco

Order No.: 51DB33MD22D1D | **GTIN (EAN):** 4069025442840


Product description: Lun21L,r.bk,wd2000lm940MLbksurf



Lunis 21 L, downlight, light control with lens, of PMMA, anti glare with reflector, matt, CAT 2 (L≤ 3000cd/m²), UGR of luminaire ≤ 19 (X = 4H | Y = 8H | S = 0.25H | reflection values 70/50/20), beam angle: wide distribution, light emission: direct distribution, LED rated luminous flux: 2.030/.../3.920lm, factory setting: 2.030lm, light colour: 940, colour temperature: 4000K, colour rendering: CRI > 90, with terminal, 3-pole, mains connection: 220..240V, AC/DC, 0/50..60Hz, rated input power: 13,3/.../26,4W, factory setting: 13,3W, luminous flux at DC operation 100%, with through-wiring, housing, round, of diecast aluminium, powder-coated, jet black (RAL 9005), diameter: 172mm, protection rating (complete): IP20, protection rating (on room side): IP54, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK03, permissible ambient temperature for indoor applications: -20..+40°C, packaging unit: 1 piece

IP 20 IK 03

Lamps:	LED
Wt. (kg):	1.4
GTIN (EAN):	4069025442840



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 19.09.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

siteco

Order No.: 51DB33MD22D1D | **GTIN (EAN):** 4069025442840

Detailed technical description: Lun21L,r.bk,wd2000lm940MLbksurf



Key data
- Product type: downlight
- Product name: Lunis 21 L
- Order No.: 51DB33MD22D1D

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:
- Light control: lens of PMMA
- Glare reduction: reflector, matt
- Beam angle: wide distribution
- Light emission: direct distribution
- UGR viewing direction along longitudinal luminaire axis: ≤ 19
- UGR viewing direction along lateral luminaire axis: ≤ 19

Lamps:
- Lamps: with LED
- Rated luminous flux: 2000lm
- Luminous efficacy: 152lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 90
- Light colour: 940
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 3 SDCM (initial)
- Rated input power: 13.3W
- Supplement: with through-wiring, luminous flux at DC operation 100%

Operating device:
- Control: ON/OFF Multilumen

Certificates, Standards
- Protection rating: IP20
- Protection rating (on room side): IP54
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK03
- Temperature range (operation): -20..+40°C
- Certification, designation: CE

Material, Colour
- housing: diecast aluminium, powder-coated, jet black (RAL 9005), round

Mounting
- Mounting method, mounting location: surface-mounted, to the ceiling
- Arrangement: single arrangement

Electrical connection
- Connection: terminal, 3-pole
- Nominal voltage: 220..240V, 0/50..60Hz, AC/DC

Dimensions, Weight
- Diameter: 172mm
- Height: 175mm
- Weight: 1.4kg

Service life
- Rated service life: 100000h (L80/B10) at AT = 25°C, 50000h (L90/B10) at AT = 25°C


It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 19.09.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

siteco

Order No.: 51DB33MD22D1D | **GTIN (EAN):** 4069025442840

Dimensions: Lun21L,r.bk,wd2000lm940MLbksurf



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 19.09.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com