siteco

Order No.: 5SLC5ECAH | **GTIN (EAN):** 4069025401311

Product description: CL-313C/R/Slave/Con/CB/ACDC



Panik Route, escape route luminaire, of PC, primary optical cover: cover, of PC, installation type: recessed, LED, rated luminous flux: 330lm, luminous efficacy: 110lm/W, light colour: 860, colour temperature: 6000K, mains connection: 230V, AC/DC, 0/50Hz, rated input power: 3W, housing, of plastic, white, length: 173mm, width: 173mm, height: 52mm, conventional central battery, protection rating (complete): IP54, insulation class (complete): insulation class II (safety insulation), permissible operating ambient temperature: 0..+45°C, packaging unit: 1 piece

IP 54

Lamps:	LED
Wt. (kg):	0.3
GTIN (EAN):	4069025401311

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 17.08.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

siteco

Order No.: 5SLC5ECAH | **GTIN (EAN):** 4069025401311

Detailed technical description: CL-313C/R/Slave/Con/CB/ACDC



Key data
- Product type: escape route luminaire
- Product name: Panik Route
- Order No.: 5SLC5ECAH

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:
- Cover: cover

Lamps:
- Lamps: with LED
- Rated luminous flux: 330lm
- Luminous efficacy: 110lm/W
- Colour temperature: 6000K
- Colour rendering index: CRI > 80
- Light colour: 860
- Rated input power: 3W
- Supplement: for central battery installations

Certificates, Standards
- Protection rating: IP54
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): 0..+45°C

Material, Colour
- housing: plastic, white
- Cover: cover of PC

Mounting
- Mounting method, mounting location: recessed, in the ceiling

Electrical connection
- Nominal voltage: 230V, 120..240V, 0/50Hz, AC/DC

Dimensions, Weight
- Length: 173mm
- Width: 173mm
- Height: 52mm
- Weight: 0.3kg

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 17.08.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com