
siteco

Order No.: 5SS3APCJ1 | **GTIN (EAN):** 4069025401427


Product description: CL-014/Slave/Con/MB/1-3hours



Panik Sign, escape sign luminaire, of PC, primary optical cover: info panel, installation type: surface-mounted, LED, light colour: 860, colour temperature: 6000K, mains connection: 230V, AC, 50Hz, rated input power: 1W, battery,battery: NiMH, 0,6Ah, housing, of plastic, white, length: 254mm, width: 254mm, height: 250mm, clamping range: 10..15mm, conventional single battery, protection rating (complete): IP42, insulation class (complete): insulation class II (safety insulation), permissible operating ambient temperature: 0..+45°C, packaging unit: 1 piece

IP 42

Lamps:	LED
Wt. (kg):	1.9
GTIN (EAN):	4069025401427




It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 28.08.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

siteco

Order No.: 5SS3APCJ1 | **GTIN (EAN):** 4069025401427

Detailed technical description: CL-014/Slave/Con/MB/1-3hours



Key data
- Product type: escape sign luminaire
- Product name: Panik Sign
- Order No.: 5SS3APCJ1

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:
- Cover: info panel

Lamps:
- Lamps: with LED
- Colour temperature: 6000K
- Colour rendering index: CRI > 80
- Light colour: 860
- Rated input power: 1W

Component 2

Lamps:
- Supplement: 1..3 hours

Operating device:
- Battery: NiMH

Certificates, Standards
- Protection rating: IP42
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): 0..+45°C

Material, Colour
- housing: plastic, white
- Cover: info panel

Mounting
- Mounting method, mounting location: surface-mounted, to wire, to the ceiling
- Clamping range: 10..15mm

Electrical connection
- Nominal voltage: 230V, 120..240V, 50Hz, AC


Dimensions, Weight
- Length: 254mm
- Width: 254mm
- Height: 250mm
- Weight: 1.9kg


It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 28.08.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com

Order No.: 5SS3APCJ1 | **GTIN (EAN):** 4069025401427

Dimensions: CL-014/Slave/Con/MB/1-3hours





It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 28.08.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -

Siteco GmbH • Georg-Simon-Ohm-Str. 50 • 83301 Traunreut, Germany • Tel +49(8669)33-0 • Fax +49(8669)33-397 • eMail info@siteco.de • Internet www.siteco.com