

Order No.: 5LZ904315 | **GTIN (EAN):** 4058352559925

Product description: SCon,controller,locCtrl



SITECO Connectcontroller, master, local control - self-sufficient standalone sensors, dimmable, installation type: recessed, installation location: in the ceiling, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, voltage: 220..240V, voltage type: AC, 1 x push button input, 1 x service push button, 1 x DALI, packaging unit: 1 piece

IP 20  

Wt. (kg): 0.1
GTIN (EAN): 4058352559925

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)
Tolerances related to thermal, electrical and photometric data according to IEC 62722
Issued 30.08.2025 - Modifications and errors subject to change - Ensure that you always use the latest version -

Order No.: 5LZ904315 | GTIN (EAN): 4058352559925

Detailed technical description: SCon,controller,locCtrl

Key data

- System family: SITECO Connect 32
- Product type: lighting management components
- Product name: SITECO Connect
- Order No.: 5LZ904315

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: DALI, dimmable

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Temperature range (operation): - 20..+60°C
- Certification, designation: CE

Material, Colour

- housing: plastic, pure white (RAL 9010)
- Colour specification: pure white (RAL 9010)

Mounting

- Mounting method, mounting location: recessed, in the ceiling
- Supplement: only suitable for use in indoor areas

Electrical connection

- Connection: terminal, 2-pole, max. 1.5mm²
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Length: 108mm
- Width: 30mm
- Height: 21mm
- Weight: 0.1kg

Inputs

1x push button input

- Connection: screw terminal, 2-pole, max. 1.5mm²
- Feature: zero-potential

1x service push button

- Option: reset

Outputs

1x DALI

- Connection: screw terminal, 2-pole, max. 1.5mm²
- System current: DALI current 96mA
- Feature: DALI, master function, broadcast addressing, max. 32 DALI ECGs