

**Order No.:** 51SD63DB11D3B | **GTIN (EAN):** 4069025539076

**Product description:** Spot21Pe,med,3060lm940,DA2ML,90,sr



Spot 21 Performance, directional spotlight, light control with lens, of PMMA, optical cover: cover panel, of glass, beam angle: medium distribution, LED rated luminous flux: 3.060lm, light colour: 940, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, of aluminium, metallic grey (RAL 9006), length: 251mm, diameter: 90mm, protection rating (complete): IP20, insulation class (complete): insulation class II (safety insulation), certification: CE, impact resistance: IK02, permissible ambient temperature for indoor applications: -20..+25°C, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	0.6
GTIN (EAN):	4069025539076



**Order No.:** 51SD63DB11D3B | **GTIN (EAN):** 4069025539076

**Detailed technical description:** Spot21Pe,med,3060lm940,DA2ML,90,sr



#### Key data

- Product type: directional spotlight
- Product name: Spot 21 Performance
- Order No.: 51SD63DB11D3B

#### Lighting technology | Lamps | Control gear

#### Component 1

#### Lighting technology:

- Light control: lens of PMMA
- Cover: cover panel
- Beam angle: medium distribution
- Symmetry: symmetric
- Secondary light control: reflector of aluminium

#### Lamps:

- Lamps: with LED
- Rated luminous flux: 3060lm
- Luminous efficacy: 150lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 90
- Light colour: 940
- SDCM (Standard Deviation of Colour Matching): MacAdam ≤ 2 SDCM (initial)
- Rated input power: 20.4W
- Supplement: luminous flux adjustable on luminaire in 12 steps (930/.../4190lm), connected load according to luminous flux setting (7/.../28.6W)

#### Operating device:

- Control: DALI 2, Multilumen

#### Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK02
- Temperature range (operation): -20..+25°C
- Certification, designation: CE

#### Material, Colour

- Cover: cover panel of glass

#### Mounting

- Mounting method, mounting location: slip-in mounting, in a 3-phase track

#### Electrical connection

- Connection: 3-phase adapter
- Nominal voltage: 220..240V, 50/60Hz, AC

#### Dimensions, Weight

- Length: 251mm
- Diameter: 90mm
- Weight: 0.6kg

#### Service life

- Rated service life: 100000h (L80/B10) at AT = 25°C, 50000h (L90/B10) at AT = 25°C

Order No.: 51SD63DB11D3B | GTIN (EAN): 4069025539076

Dimensions: Spot21Pe,med,3060lm940,DA2ML,90,sr



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at [www.siteco.com](http://www.siteco.com))

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 15.05.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -