

Order No.: 51SE137BB3B | **GTIN (EAN):** 4058352609668

Product description: Spot21std,med,2700lm930,0/1,105,wh



Spot 21 standard, directional spotlight, light control with reflector, of aluminium, beam angle: medium distribution, LED rated luminous flux: 2.700lm, light colour: 930, control gear: ECG, with 3-phase adapter, mains connection: 220..240V, AC, 50/60Hz, housing, of aluminium, traffic white (RAL 9016), diameter: 105mm, adapter, of plastic, protection rating (complete): IP20, insulation class (complete): insulation class I (protective earthing), certification: CE, impact resistance: IK02, packaging unit: 1 piece

IP 20  

Lamps:	LED
Wt. (kg):	0.8
GTIN (EAN):	4058352609668



Order No.: 51SE137BB3B | GTIN (EAN): 4058352609668

Detailed technical description: Spot21std,med,2700lm930,0/1,105,wh



Key data

- Product type: directional spotlight
- Product name: Spot 21 standard
- Order No.: 51SE137BB3B

Lighting technology | Lamps | Control gear

Component 1

Lighting technology:

- Light control: reflector of aluminium
- Beam angle: medium distribution
- Symmetry: symmetric

Lamps:

- Lamps: with LED
- Rated luminous flux: 2700lm
- Colour temperature: 3000K
- Colour rendering index: CRI > 90
- Light colour: 930

Operating device:

- Control gear: ECG
- Control: ON/OFF

Certificates, Standards

- Protection rating: IP20
- Insulation class: insulation class I (protective earthing)
- Impact resistance: IK02
- Certification, designation: CE

Material, Colour

- housing: aluminium, traffic white (RAL 9016)
- adapter: plastic

Electrical connection

- Connection: 3-phase adapter
- Nominal voltage: 220..240V, 50/60Hz, AC

Dimensions, Weight

- Diameter: 105mm
- Weight: 0.8kg

Service life

- Rated service life: 50000h (L80/B50) at AT = 25°C

Order No.: 51SE137BB3B | GTIN (EAN): 4058352609668

Dimensions: Spot21std,med,2700lm930,0/1,105,wh



It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 23.05.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -