

Order No.: 5EA40TMC01 | **GTIN (EAN):** 4069025815682

Product description: SConWi,SmartPlugMot2PIRCAS



SITECO Connect WirelessSmart Plug Motion 2PIR Casambi, luminaire controller, communication: 2.4GHz, local mesh radio network, Bluetooth, D4i type A, control: local setting and operation with smartphone app, manual, by daylight, optionally via radio push button, by movement, sensor technology: daylight sensor, 2 PIR movement sensors, configuration via Casambi app, Compatible only with ECGs with logarithmic DALI dimming curve, optional remote setup and operation via gateway, installation type: screw fastening, installation location: to the luminaire, Smart Interface below: Zhaga, of plastic, voltage: 12..20V, voltage type: DC, PIR movement sensor, protection rating (complete): IP66, certification: CE, UKCA, packaging unit: 1 piece

IP 66 IK 08 

Wt. (kg): 0.1
GTIN (EAN): 4069025815682

Order No.: 5EA40TMC01 | **GTIN (EAN):** 4069025815682

Detailed technical description: SConWi,SmartPlugMot2PIRCAS

Key data

- System family: SITECO Connect 31 Wireless
- Product type: luminaire controller
- Product name: SITECO Connect Wireless
- Order No.: 5EA40TMC01

Lighting technology | Lamps | Control gear

Component 1

Operating device:

- Control: D4i, Casambi, configuration via Casambi app, Compatible only with ECGs with logarithmic DALI dimming curve, optional remote setup and operation via gateway

Certificates, Standards

- Protection rating: IP66
- Impact resistance: IK08
- Temperature range (operation): -20...+50°C
- Standard: according to Zhaga book 18
- Certification, designation: CE, UKCA

Material, Colour

- housing: plastic, grey

Mounting

- Mounting method, mounting location: screw fastening, to the luminaire

Electrical connection

- Nominal voltage: 12..20V, DC

Dimensions, Weight

- Weight: 0.1kg

Inputs

PIR movement sensor

- Detection range: max. 35x16m