

Order No.: 58WB1O1B | **GTIN (EAN):** 4069025723482

Product description: RON21emerg.lght.elem,LED,260lm840,PC,rec

Rondel 21, emergency light element, primary light control with lens, of PC, installation type: recessed, emergency light element,LED, rated luminous flux: 260lm, luminous efficacy: 100lm/W, light colour: 840, colour temperature: 4000K, control gear: DALI 2, with terminal, 5-pole, mains connection: 220..240V, AC, 50/60Hz, rated input power: 2W, housing, round, of PC, graphite (RAL 7037), diameter: 266mm, height: 44mm, protection rating (complete): IP40, insulation class (complete): insulation class II (safety insulation), certification: CE, impact resistance: IK03, permissible operating ambient temperature: 0..+40°C, standard: EN 60598-2-22, self-test according to IEC 62034, packaging unit: 1 piece

IP 40 IK 03  

Lamps:	LED
Wt. (kg):	0.3
GTIN (EAN):	4069025723482

Order No.: 58WB1O1B | **GTIN (EAN):** 4069025723482

Detailed technical description: RON21emerg.lght.elem,LED,260lm840,PC,rec

Key data

- Product type: emergency light element
- Product name: Rondel 21
- Order No.: 58WB1O1B

Dimensions, Weight

- Diameter: 266mm
- Height: 44mm
- Weight: 0.3kg

Lighting technology | Lamps | Control gear

Service life

- Rated service life: 25000h (L80) at AT = 25°C

Component 1

Lighting technology:

- Light control: lens

Lamps:

- Lamps: with LED
- Rated luminous flux: 260lm
- Luminous efficacy: 100lm/W
- Colour temperature: 4000K
- Colour rendering index: CRI > 80
- Light colour: 840
- Rated input power: 2W
- Supplement: for emergency light function

Operating device:

- Control: DALI 2

Certificates, Standards

- Protection rating: IP40
- Insulation class: insulation class II (safety insulation)
- Impact resistance: IK03
- Temperature range (operation): 0...+40°C
- Supplement: self-test according to IEC 62034
- Standard: EN 60598-2-22
- Certification, designation: CE

Material, Colour

- housing: PC, graphite (RAL 7037), round

Mounting

- Mounting method, mounting location: recessed, in the luminaire

Electrical connection

- Connection: terminal, 5-pole
- Nominal voltage: 220...240V, 50/60Hz, AC
- Battery supply: incl. 3.6V NiCd battery

It is mandatory that the assembly instructions must be observed when planning and installing the electrical installation (to be found at www.siteco.com)

Tolerances related to thermal, electrical and photometric data according to IEC 62722

Issued 11.07.2026 - Modifications and errors subject to change - Ensure that you always use the latest version -